



INTERCHANGEABLE HEAD TORQUE WRENCHES

Features

- Interchangeable heads permit ratcheting, fixed, or open end torquing capability with adjustable torque wrench bodies.
- A push of the locking pin provides quick-change action, with a wide range of head styles to choose from.
- Micrometer Type Adjustment-ensures fast, accurate settings and changes.
- *Part Number 800NMIMH has Dual Pin Release for added strength

INTERCHANGEABLE HEAD TORQUE WRENCHES - DUAL SCALE

| Product Code | Shank Size | Nm Range | Incr. | English Range |
|--------------|------------|-----------|-------|---------------|
| 50NMIMH | J | 10 - 50 | 0.5 | 7.4 - 44.2 |
| 100NMIMH | J | 20 - 100 | 0.5 | 14.8 - 73.8 |
| 200NMIMH | Y | 40 - 200 | 2 | 29.5 - 147.5 |
| 350NMIMH | X | 70 - 350 | 2 | 44.3 - 250.8 |
| 800NMIMH* | Z | 150 - 800 | 5 | 110.6 - 590 |

INTERCHANGEABLE HEAD TORQUE WRENCHES - SINGLE SCALE

| Product Code | Shank Size | English Range | Incr. |
|--------------|------------|---------------|-------|
| 75MFIMHSS | J | 5 - 75 | 0.5 |
| 150MFIMHSS | Y | 20 - 150 | 1 |
| 250MFIMHSS | Y | 30 - 250 | 1 |



SINGLE SETTING TORQUE WRENCHES

Single setting torque wrenches are designed for use on production lines and other applications where a specific torque is required for repetitive operations.

Features

- Factory Pre-Set models are set at the factory to the customer's specified torque setting, and are furnished with a Certificate of Calibration.
- Please specify desired torque setting when order is placed.
- Featuring a durable, non-slip cushion grip
- Uses universal round shank interchangeable heads
- Audible click and feel impulse torque control mechanism
- Tamper proof torque setting for production line use
- Accuracy: $\pm 4\%$ of indicated value, in direction of torque indicator, from 20% to 100% of full scale
- Meets or exceeds ASME B107.14-2004, ISO 6789

SINGLE SETTING TORQUE WRENCHES

| Product Code Un-Set | Product Code Factory Pre-Set | English Range | Nm Range | Shank Size | A In. | B In. | C In. | D In. | Wt. Lbs. |
|---------------------|------------------------------|-------------------|-----------|------------|-------|-------|-------|-------|----------|
| 5T-I | 5T-I-SET | 10 - 50 in. lb. | 1.1 - 5.6 | J | 6.5 | 0.63 | 0.61 | 1 | 0.35 |
| 10T-I | 10T-I-SET | 50 - 250 in. lb. | 5.6 - 28 | J | 10 | 0.63 | 0.61 | 1 | 0.55 |
| 10ST-I | 10ST-I-SET | 60 - 300 in. lb. | 6.8 - 34 | J | 6.2 | 0.68 | 0.86 | 1.4 | 0.75 |
| 50T-I | 50T-I-SET | 15 - 75 ft. lb. | 20 - 102 | J | 11 | 0.68 | 0.96 | 1.4 | 1.4 |
| 100T-I | 100T-I-SET | 30 - 150 ft. lb. | 41 - 203 | Y | 19.5 | 0.94 | 0.96 | 1.4 | 2.3 |
| 200T-I | 200T-I-SET | 40 - 200 ft. lb. | 54 - 271 | Y | 23.5 | 0.94 | 0.86 | 1.4 | 2.6 |
| 300T-I | 300T-I-SET | 100 - 300 ft. lb. | 135 - 406 | X | 27.7 | 1.12 | 1 | 1.4 | 3.9 |
| 600T-I | 600T-I-SET | 120 - 600 ft. lb. | 162 - 814 | Z | 55 | 1.5 | 1.25 | 1.25 | 10.45 |



*Note: 800NMIMH new dual pin "Z" receivers accept only dual pin interchangeable heads.

