

Eagle Pro Industrial EPA Series Ultra-High Pressure Hand Pumps



MODEL	CYLINDER TYPE	SPEED	USABLE OIL VOLUME	PRESSURE RATING		OIL DISPLACEMENT		HANDLE FORCE	PORT THREAD	A	B	C	D	E	F	G	H	WEIGHT
				1ST STAGE	2ND STAGE	1ST STAGE	2ND STAGE											
			IN3	PSI	PSI	IN3	IN3	LBS	IN	IN	IN	IN	IN	IN	IN	IN	IN	IN
EPA-10521 *	SINGLE ACTING	TWO	20	200	10,000	0.48	0.05	77	3/8- 18NPT	14.74	11.40	-	3.14	4.30	2.63	-	5.60	4.80
EPA-10921A			55	360	10,000	2.04	0.20	108		22.89	19.87	1.85	4.24	5.10	3.22	3.22	6.50	16.06
EPA-12321A			140	360	10,000	0.04	0.20	108		29.04	19.96	1.85	4.91	5.40	-	3.22	6.34	22.22
EPA-14 521			275	260	10,000	1.59	0.18	112		22.80	23.90	6.40	10.80	12.40	9.80	-	10.50	49.50
EPA-17521	DOUBLE ACTING		458	260	10,000	7.6	0.35	112		31.50	35.60	8.90	10.80	12.40	9.80	-	12.40	66.00
EPA-10922A			55	360	10,000	2.04	0.20	108		22.89	19.87	1.14	4.24	4.20	3.22	3.22	6.50	19.36
EPA-12322A			140	360	10,000	2.04	0.20	108		29.04	19.96	1.14	4.91	4.20	-	3.22	6.34	25.52
EPA-14 522			275	260	10,000	1.59	0.18	112		22.80	23.90	6.40	10.80	12.40	9.80	-	10.50	49.50
EPA-17522	458	260	10,000	7.6	0.35	112	31.50	35.60	8.90	10.80	12.40	9.80	-	12.40	66.00			
EPA-21621	BOLT TENSIONER		98	290	20,000	1.95	0.05	44	1/4BSP	**							20.9	