

# Eagle Pro Industrial ESP Series Ram Pull-Back



MODEL	CYLINDER CAPACITY @ 10,000 PSI (700 BAR)	STROKE	CYLINDER EFFECTIVE AREA	OIL CAPACITY	EXTENDED	COLLAPSED	OUTSIDE	PISTON	TOP TO	SADDLE	PISTON	PISTON DIAMETER	BASE MOUNTING HOLE	COLLAR THREAD	COLLAR THREAD LENGTH	BASE MOUNTING HOLE THREAD	WEIGHT
					HEIGHT	HEIGHT	DIAMETER	DIAMETER	INLET PORT	DIAMETER	THREAD LENGTH						
					A	B	D	F	H	J	P						
METRIC TON (US TON)		IN	IN2	IN3	IN	IN	IN	IN	IN	IN	IN	IN	IN	IN	IN	IN	LBS
ESP-25	2.5 (2.75)	5.00	0.61	3.04	15.39	10.39	1.95	0.79	1.77	3/4 - 14	0.87	1-1/16 - 24	3/4 - 14NPT	-1/2 - 16UNF	1.06	0.67	3.96
ESP-46	5 (5.5)	5.51	1.16	6.41	17.36	11.85	2.25	1.18	1.65	1-1/4 - 11-1/2	1.10	1-3/16 - 16	-1/4 - 11-1/2NPT	-1/4 - 14UNF	1.02	0.94	9.90
ESP-106	10 (11)	5.94	2.19	13.02	17.32	11.38	3.35	1.38	1.54	-	0.79	M30 X 2	M30 X 2	M85 X 2	0.98	1.06	20.90

MODEL	CYLINDER CAPACITY @ 10,000 PSI (700 BAR)	STROKE	CYLINDER EFFECTIVE AREA	OIL CAPACITY	EXTENDED	COLLAPSED	OUTSIDE	LINK	LINK LENGTH	LINK BOLT	LINK	LINK END WIDTH	WEIGHT
					HEIGHT	HEIGHT	DIAMETER	WIDTH	LENGTH	DIAMETER	OPENING		
					A	B	D	J	L	M	N		
METRIC TON (US TON)		IN	IN2	IN3	IN	IN	IN	IN	IN	IN	IN	IN	LBS
ESP-106C	10 (11)	5.94	2.19	13.02	29.06	23.11	3.35	4.69	2.44	1.18	1.38	1.26	35.20
ESP-106L					27.24	21.30		2.52	4.53	0.87	1.18	1.26	29.26
ESP-306	30 (33)	6.10	7.40	45.11	48.82	42.72	5.35	4.49	5.71	1.38	1.54	1.97	106.04
ESP-606	50 (55)	5.98	11.05	66.11	34.29	28.31	5.51	5.12	5.87	1.57	1.97	2.76	117.92